

**CLAIMS**

I claim:

1. A surface scanned by an optical sensor of a relative position determinator, for use with a light source, comprising:

first regions that reflect light beams from the light source toward the optical sensor, in the form of reflected light beams; and

second regions that reflect light from the light source away from the optical sensor, in the form of deflected light beams, the reflected light beams and the deflected light beams together forming an image used by the relative position determinator to detect change in the position of the optical sensor relative to the surface.

2. The surface as in claim 1, wherein the first regions are specular.

3. The surface as in claim 2, wherein the second regions are specular.

4. The surface as in claim 3, wherein the first regions are selected from a group consisting of surfaces containing depressions, surface protrusions, and a combination of surfaces containing depressions and surface protrusions.

5. The surface as in claim 4, wherein the first regions are rotationally symmetric.

6. The surface as in claim 5, wherein the first regions are sized to be detectable by the optical sensor.

7. The surface as in claim 6, wherein the second regions surround the first regions.

8. The surface as in claim 7, wherein the surface is covered with an optically transparent coating.

9. A surface scanned by an optical sensor of a relative position determinator, for use with a light source, comprising:

regions of a first reflectance that reflect light beams from the light source in the form of a first set of reflected light beams; and

regions of a second reflectance, less reflective than the regions of the first reflectance, that reflect light beams from the light source in the form of a second set of reflected light beams, the first set of reflected light beams and the second set of reflected light beams together forming an image used by the relative position determinator to detect change in the position of the optical sensor relative to the surface.

10. The surface as in claim 9, wherein the regions of the first reflectance are a first color, and the regions of the second reflectance are a second color, darker than the first color.

11. The surface as in claim 10, wherein the regions of the first color are high-reflectance, and the regions of the second color are low-reflectance.

12. The surface as in claim 11, wherein the regions of the first color are sized to be detectable by the optical sensor.

13. A method for determining the position of an optical sensor relative to a surface, wherein the optical sensor is part of a relative position determinator, to be used with a light source that illuminates the surface, comprising the steps of:

shining light from the light source onto the surface;

reflecting light from a first group of regions on the surface toward the optical sensor, in the form of reflected light beams;

reflecting light from a second group of regions on the surface away from the optical sensor, in the form of deflected light beams;

294  
293  
292  
291  
290  
289  
288  
287  
286  
285  
284  
283  
282  
281  
280  
279  
278  
277  
276  
275  
274  
273  
272  
271  
270  
269  
268  
267  
266  
265  
264  
263  
262  
261  
260  
259  
258  
257  
256  
255  
254  
253  
252  
251  
250  
249  
248  
247  
246  
245  
244  
243  
242  
241  
240  
239  
238  
237  
236  
235  
234  
233  
232  
231  
230  
229  
228  
227  
226  
225  
224  
223  
222  
221  
220  
219  
218  
217  
216  
215  
214  
213  
212  
211  
210  
209  
208  
207  
206  
205  
204  
203  
202  
201  
200  
199  
198  
197  
196  
195  
194  
193  
192  
191  
190  
189  
188  
187  
186  
185  
184  
183  
182  
181  
180  
179  
178  
177  
176  
175  
174  
173  
172  
171  
170  
169  
168  
167  
166  
165  
164  
163  
162  
161  
160  
159  
158  
157  
156  
155  
154  
153  
152  
151  
150  
149  
148  
147  
146  
145  
144  
143  
142  
141  
140  
139  
138  
137  
136  
135  
134  
133  
132  
131  
130  
129  
128  
127  
126  
125  
124  
123  
122  
121  
120  
119  
118  
117  
116  
115  
114  
113  
112  
111  
110  
109  
108  
107  
106  
105  
104  
103  
102  
101  
100  
99  
98  
97  
96  
95  
94  
93  
92  
91  
90  
89  
88  
87  
86  
85  
84  
83  
82  
81  
80  
79  
78  
77  
76  
75  
74  
73  
72  
71  
70  
69  
68  
67  
66  
65  
64  
63  
62  
61  
60  
59  
58  
57  
56  
55  
54  
53  
52  
51  
50  
49  
48  
47  
46  
45  
44  
43  
42  
41  
40  
39  
38  
37  
36  
35  
34  
33  
32  
31  
30  
29  
28  
27  
26  
25  
24  
23  
22  
21  
20  
19  
18  
17  
16  
15  
14  
13  
12  
11  
10  
9  
8  
7  
6  
5  
4  
3  
2  
1  
0  
forming an image with the reflected and deflected light beams, the image used by the relative position determinator to detect change in the position of the optical sensor relative to the surface.

---

14. The method of claim 13, wherein the first group of regions is specular.

15. The method of claim 14, wherein the second group of regions is specular.

16. The method of claim 15, wherein the first group of regions is made up of rotationally symmetric elements.

17. The method of claim 16, wherein the surface is covered with an optically transparent coating.

18. The method of claim 17, wherein the first group of regions is made up of surfaces containing depressions.

19. The method of claim 18, wherein the first group of regions is made up of surfaces containing protrusions.

---